

Rolling Shutters

(Extruded Aluminum)

4000 Series - Florida Building Code & Dade County Approved.

Our “**4000 Series**” 40mm **Extruded Aluminum** shutter has a smaller interlocking slat profile and can roll up into a smaller housing than the 55mm slat profile. It is designed for **storm protection** and security for **smaller openings** and areas with limited head room.

You can use the 40mm formula found on the “**Box Size and Capacity Chart**” page to determine the finished shutter size and square footage. This will help you pick the method of operation needed. Any of the operation methods are usable with the 4000 series shutter considering you don't exceed the maximum weight limitations.

The **pull strap system** can be used up to 25 square feet of the finished sized shutter.

It can be **manually cranked** up to 75 square feet of finished size shutter with the use of an assist spring. Any shutter larger than 75 sq ft will require a **motorized system**. A motor can be added as an option with a shutter of any size.

Storm bars and header may be required in certain zoned areas for openings larger than 48” in width. They will help reduce the amount of flexing during maximum wind pressures of 150 mph.

The “**4000 Series**” shutter system is used in residential homes, apartments, businesses, store fronts, high-rise buildings and condominiums, over garage doors, carports, trash areas and many other places where **maximum hurricane and security** protection are needed. They can be used **inside** as a safe room retreat or as a partition between rooms as well. There are unlimited possibilities and options for this shutter depending on your needs.